

White Silicone Roof Sealant & Patch

For Patching and Repairing Roof Surfaces

50 Year Protection



Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

100% Silicone high solids sealant designed for a variety of roofing repair applications. Forms a tough, durable water proof and UV resistant rubber sealant.

Uses

Smooth surface BUR, modified Bitumen (MB), granulated cap sheet, well-adhered acrylic coating, concrete, metal, sprayed-in-place polyurethane foam, TPO, EPDM, PVC, Hypalon and various single-ply membrane roofing and flat roof applications.

Surface Preparation

Surface shall be clean, dry and free of loose particles. Remove any rust, mildew, oil, grease or other foreign material on the surface.

Application

Completely fill cracked or damaged areas. For cracks greater than 1/2" use with SealBest Roofing Fabric to reinforce repair. On 10 oz tube, cut tip on angle. Puncture foil at inner base of nozzle. Place tube in caulking gun and squeeze trigger to begin flow.

Smooth out silicone bead with putty knife or similar tool. Spread material up to 1" beyond sides of crack and feather out into surrounding surface. Material will be tack free within 1 to 2 hours and fully cured within 48 hours.

Clean Up

Clean uncured material from tools and equipment with VM&P Naphtha or Mineral Spirits.

Weather Conditions

- Surface and air temperature shall be between 40°F and 100°F.
- Surface shall be completely dry (no moisture or dew).

Coverage (Approximate)

Approximately 50 linear feet per 3/16" bead.

Precautions

- Do Not Heat or Thin
- Do Not Freeze
- Do Not Store at Temperatures Below 50 °F

Safety & Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container when Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is less than 50 gm/liter
- KEEP OUT OF REACH OF CHILDREN

Ingredients:	Cas No.
Nepheline syenite	37244-96-5
Polysiloxanes	Trade Secret
Polyoxydimethylsilylene	9016-00-6
Amorphous Fumed Silica	112945-52-5
Methylsilylidynetroxime	22984-54-9
Titanium Dioxide	13463-67-7

White Silicone Roof Sealant - 50 Year Protection

Revised: 03/20