

Professional Grade Pourable Concrete Crack Sealant

100% Acrylic Formula



Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

Concrete Crack Sealant is a 100% acrylic elastomeric sealant designed for filling cracks up to 1/2" wide in concrete pavement surfaces.

Uses

Ideal for use on all types of concrete surfaces.

Coverage

Coverage is dependent upon depth and width of cracks. Typically, one quart of Concrete Crack Sealant will fill approximately 20-35 feet of cracks.

Directions

CLEAN CRACKS- Remove dirt and vegetation from cracks with screwdriver or other suitable instrument. Flush out crack with water and allow to dry.

APPLYING CONCRETE CRACK SEALANT- Mix contents of container by moderately shaking. Cut top of spout to desired width (smaller than width of crack). Fill cracks and smooth flush to adjoining pavement with putty knife. Allow crack sealant to dry for 24 hours. If desired, a second application may be applied.

Drying Time

Allow Crack Sealant to cure 24 hours before resuming traffic.

Clean Up

Wash tools with water before material dries.

Important

Read entire label before using. Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a 24 hour period. Be sure to wear eye protection, gloves, long pants, and long sleeves when mixing and applying SealBest materials. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog,

or rain arrive before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Use Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 50 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Water	7732-18-5
Acrylic Emulsion Polymer	Proprietary
Silicon Dioxide	14808-60-7

Professional Grade Pourable Concrete Crack Sealant

Revised: 01/11