

# Acrylic Modified Pourable Crack Filler

Flexible Asphalt Emulsion



## Manufacturer:

ThorWorks Industries, Inc.  
2520 S. Campbell St.  
Sandusky, OH 44870  
Phone: 800-326-1994  
Fax: 419-626-5477

## Description

SealBest Acrylic Modified Pourable Crack Filler is an asphalt emulsion crack filler designed for sealing cracks up to 1/2" wide in asphalt pavement surfaces. Dries Black.

## Uses

Fills and seals cracks up to 1/2" wide.

## Coverage

One .9 gallon of SealBest Acrylic Modified Pourable Crack Filler will fill approximately 75-150 feet of cracks. Ultimate coverage will be dependant upon depth and width of cracks.

## Directions

**CLEAN CRACKS:** Use a screwdriver, brush, or other suitable tool to remove dirt, debris, and vegetation from cracks. Clean out cracks with water. Allow cracks to dry prior to filling.

**APPLICATION:** Mix contents of container by moderately shaking. Cut top of spout to desired width (smaller than width of crack). Fill cracks even to adjoining pavement. If desired, a second application of crack filler may be applied to compensate for shrinkage from evaporation of the first application. All of crack filler to dry for 24 hours prior to applying driveway sealer.

## Drying Time

Up to 24 hours depending upon weather conditions.

## Clean Up

Wash tools with water before material dries.

## Important

Read entire label before using. Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a 24 hour period. Be sure to wear eye protection, gloves, long pants, and long sleeves when mixing and applying SealBest materials. In areas where dew or fog accumulates in the early evening, it is best to coat in the

morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrive before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application. DO NOT USE ON CONCRETE SURFACES.

## Precautions

- Do Not Heat Or Thin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

## Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 10 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Asphalt	8052-42-4
Clay	1332-58-7
Polymer Latex	Proprietary
Water	7732-18-5

Acrylic Modified Pourable Crack Filler

Revised: 01/11