Acrylic Fence & Barn Paint

Environmentally Friendly Formulation



Manufacturer:

ThorWorks Industries, Inc. 2520 S. Campbell St. Sandusky, OH 44870 Phone: 800-326-1994

Description

Fax: 419-626-5477

Quality acrylic fence paint designed to beautify and protect wood plank fences, barns and more. Environmentally friendly water-based formula

Uses

Ideal for all wood plank fences, all types of barns, roofs, concrete, and more

Coverage

Up to 95-100 square feet per gallon per coat depending upon porosity of surface.

Directions

SURFACE PREPARATION- Surface shall be clean, dry and free of any dirt or contaminants.

APPLICATION- Stir container thoroughly. Apply by brush, roller or airless spray (suggested tip size minimum .017 to .021).

Drying Time

Dry to the touch in 2-3 hours. Allow 6-8 hours before applying second coat.

Clean Up

Wash tools with water before material dries.

Important

Read entire label before using. Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24 hour period. Be sure to wear eye protection, gloves, long pants, and long sleeves when mixing and applying SealBest materials. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrive before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

Precautions

- Do Not Heat OrThin
- Do Not Freeze
- Do Not Store At Temperatures Below 50 °F

Safety And Environmental Precautions

- · Refer To Material Safety Data Sheet Before Using
- · For Exterior Use Only
- Apply In A Well Ventilated Area
- · Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) 100 Gm/Liter Max
- · Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Acrylic Emulsion Polymer	Proprietary
Carbon Black	1333-86-4
Ethelene Glycol	107-21-1
Texanol	25265-77-4

Revised: 01/11