

# Professional Grade Asphalt Fibered Roof Coating

Forms A Tough, Adhesive Bond



## Manufacturer:

ThorWorks Industries, Inc.  
2520 S. Campbell St.  
Sandusky, OH 44870  
Phone: 800-326-1994  
Fax: 419-626-5477

## Description

A mixture of liquid asphalt and fibers which forms a tough, durable adhesive bond with most roof surfaces. Highly resistant to water and other types of weather damage. Seals small cracks, joints, seams, and nail holes.

## Uses

Metal Roofs, Built-Up Roofs, Roof Felts, Concrete Roofs, and Concrete Foundations

## Coverage

Metal Roofs: 60-70 Square Feet per Gallon  
Felt or Composition Roofs: 50-60 Square Feet per Gallon  
Concrete or Masonry: 25-50 Square Feet per Gallon  
Strip Composition or Dried Out Roofing: 25-50 Square Feet per Gallon

## Directions

**CLEAN AND REPAIR ROOF-** Clean surface with brush or boom, removing all loose sediment and dirt. Nail down any loose parts. Repair any leaking or weak areas with SealBest All-Weather Roof Cement and Asphalt Coated Reinforcing Fabric, adhering to the directions on their label.

**APPLYING ROOF COATING-** Mix coating thoroughly before and during application. Then coat entire surface area with SealBest Fibered Roof Coating. For best results, apply a uniform coating with roofing brush when surface is dry. One coat provides year round protection.

## Drying Time

Allow 24 hours, depending on weather conditions.

## Clean Up

Clean tools with mineral spirits before material has dried.

## Important

Read entire label before using. Be sure to wear eye protection, gloves, long pants, and long sleeves when mixing and applying SealBest materials. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrive before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

## Precautions

- Combustible. Contains Petroleum Distillate.
- Do Not Heat Or Thin
- Keep Away From Heat And Flame
- Do Not Store At Temperatures Above 100 °F

## Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Use Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 250 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Asphalt	8052-42-4
Mineral Spirits	64742-88-7
Calcium Carbonate	1317-65-3
Cellulose Fibers	9004-34-6
Magnesium Carbonate	546-93-0

Professional Grade Asphalt Fibered Roof Coating

Revised: 01/11