

Professional Grade Fibered Aluminum Roof Coating

Formulated for Premium Reflectivity



Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

SealBest Fibered Aluminum Roof Coating is a premium professional grade contractor proven blend of select waterproofing asphalts and high quality leafing aluminum pigments. When applied as directed, it cures to a brilliant decorative coating, providing maximum protection and durability against the elements. It reflects up to 90% of the sun's rays and reduces roof temperature by 15-20° F., increasing roof life and lowering energy costs.

Uses

For a variety of surfaces, such as Metal, Concrete, and Built-Up Roofs, Mod. Bitumen SBS/APP, Weathered Asphalt Coatings, Metal Buildings, Grain Bins, and Mobile Homes.

Coverage

Metal Roofs - 75-100 Square Feet per Gallon
Composition Roofs - 50-75 Square Feet per Gallon

Directions

CLEAN AND REPAIR ROOF- Repair all cracks, splits, and holes using SealBest All-Weather Roof Cement and Asphalt Coated Reinforcing Fabric, adhering to the directions on their label. Allow repairs to weather at least 30 days before coating. Clean surfaces thoroughly by brooming away dirt, dust and loose particulate. Remove all grease and oil using detergent and water, rinsing thoroughly. Broom away excess water and allow to dry completely.

APPLYING ROOF COATING- Mix coating thoroughly before and during application. Uniformly coat the entire surface with the coating using a roofing brush or roller. Do not apply to roofs which hold water. Standing water will result in premature failure.

Drying Time

Allow 24 hours, depending on weather conditions.

Clean Up

Clean up with waterless hand cleaner or mineral spirits immediately after use.

Important

Read entire label before using. Application temperature must be a minimum of 50 °F and rising. Do not apply when temperature is expected to drop below 50 °F within a 24 hour period. Be sure to wear eye protection, gloves, long pants, and long sleeves when mixing and applying SealBest materials. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrive before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

Precautions

- Combustible. Contains Petroleum Distillate.
- Do Not Heat Or Thin
- Keep Away From Heat And Flame
- Do Not Store At Temperatures Above 100 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Use Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 500 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Asphalt	8052-42-4
Stoddard Solvent	64742-88-7
Aluminum Flake	7429-90-5
Cellulose	9004-34-6
Calcium Carbonate	1317-65-3

Professional Grade Fibered Aluminum Roof Coating

Revised: 01/11