

Professional Grade Cold Process Blind Nail & Lap Adhesive

Blind Nailing Cement for Roll Roofing



Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

A special blend of adhesive asphalts, fibers, special resins, and other ingredients that assure its rapid fusion to the base surface. Intended primarily as a blind nailing cement for use with roll roofing. It creates a tight bond and prevents buckling and curling of edges. Roof adhesive is also suitable for application to older roofs to seal cracks and pinholes. Dries Black.

Uses

Adhesive for Rolled Roofing

Coverage

Approximately 50 Square Feet Per Gallon. 150 - 175 linear feet per 4 inch lap.

Directions

CLEAN AND REPAIR ROOF- Clean surface with brush or boom, removing all loose sediment and dirt. Nail down any loose parts.

APPLYING ROOF COATING- Apply with a roofer's brush or masonry trowel in a uniform consistency. Apply a sufficient amount of adhesive to cover the entire underside of the membrane and to allow a 1/8" - 1/4" bead of adhesive to form along the lap seam when membrane is pressed into place. Broom or walk the overlying sheet firmly into the cement and smooth it out to prevent buckles or blisters.

Drying Time

Allow 24 hours, depending on weather conditions.

Clean Up

Clean tools with mineral spirits before material has dried.

Important

Read entire label before using. Be sure to wear eye protection, gloves, long pants, and long sleeves when mixing and applying SealBest materials. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrive before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

Precautions

- Combustible. Contains Petroleum Distillate.
- Do Not Heat Or Thin
- Keep Away From Heat And Flame
- Do Not Store At Temperatures Above 100 °F

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Use Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 300 Gm/Liter Max
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Asphalt	8052-42-4
Mineral Spirits	64742-88-7
Calcium Carbonate	1317-65-3
Cellulose Fibers	9004-34-6
Magnesium Carbonate	546-93-0
Amine Salt	Not Est'd

Professional Grade Cold Process Blind Nail & Lap Adhesive

Revised: 01/11