



Non-Fibered Foundation Coating

Asphalt Based Coating

Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

A sealer-preservative for all types of surfaces, this product is an excellent saturant for composition roofing which has become excessively dry. It rustproofs metal, preserves wood, waterproofs stone or brick and rejuvenates composition surfaces. Also used to coat concrete foundations, above or below grade as well as fences and barns. Dries black. Meets ASTM D 41.

Uses

- Most Roof Surfaces, Concrete Foundations, Wood Fences and Barns

Surface Preparation

For best results, clean surface with brush or broom, removing all loose sediment and dirt. Nail down any loose parts. Repair any leaking or weak areas with roof cement and fabric repair material.

Application

Stir container before and during use. Coat entire surface area with SEALBEST Non-Fibered Foundation Coating. Material may be brushed or sprayed using a minimum 500 psi airless sprayer. Porous surfaces may require two applications. Do not apply on any wet surface.

Drying Time

Allow 24 hours depending on weather conditions.

Clean Up

Clean tools with mineral spirits or kerosene in a well ventilated area immediately after use.

Weather Conditions

- Do not apply if rain is imminent within 24 hours of application.

Coverage (Approximate)

- Metal Surfaces: 90-100 sq. ft. per gallon
- Concrete and Masonry Surfaces: 75-100 sq. ft. per gallon
- Wood or Composition: 65-90 sq. ft. per gallon
- Worn Roofing: 50-80 sq. ft. per gallon

Precautions

- Do Not Heat Or Thin
- Do Not Store At Temperatures Above 100 °F
- Do Not Apply Over Coal Tar Surfaces
- Do Not Apply Where Hydrostatic Pressures Could Be Encountered
- Combustible. Contains Petroleum Distillate

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) Is 300 gm/liter max
- Use With Adequate Ventilation
- KEEP OUT OF REACH OF CHILDREN

Ingredients:	Cas No.
Petroleum Asphalt	8052-42-4
Mineral Spirits	64742-88-7

Non-Fibered Foundation Coating - Asphalt Based Coating

Revised: 03/08