

Professional Grade Neoprene Roof Cement

Elastomeric Flashing and Repair Product



Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

A polymer-modified asphalt adhesive designed for use with rolled materials as well as patching and repair.

Uses

Use for various roof repairs including vent pipes, skylights, chimneys, roof vents, BUR, and SBS membrane systems.

Coverage

Coverage will vary with thickness of application but will approximate 30 lineal ft. per cartridge (1/4" thick).

Directions

SURFACE PREPARATION- All surfaces to be treated must be free from oil, grease and other foreign materials prior to application. The surface must be firm and free from loose material. On composition roofs, open any breaks or blisters to be patched and permit to dry out before applying this product.

APPLYING MASTIC- Trim nozzle to desired bead size. Puncture foil at innerbase of nozzle. Using a caulking gun, apply to a minimum wet thickness of 1/4". Allow at least 24 hours to dry (70°F and less than 50% humidity with no rain) before applying a surface coating. Use above or below grade.

Drying Time

Approximately 24, dependant upon thickness of application and weather conditions.

Clean Up

Clean tools with mineral spirits before material has dried.

Important

Read entire label before using. Be sure to wear eye protection, gloves, long pants, and long sleeves when mixing and applying SealBest materials. In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent

wash off, which will occur if dew, fog, or rain arrive before coating dries. Do not apply if rain is imminent or forecast within 24 hours of application.

Precautions

- Combustible. Contains Petroleum Distillate.
- Do Not Heat Or Thin
- Keep Away From Heat And Flame
- Do Not Store At Temperatures Above 100 oF

Safety And Environmental Precautions

- Refer To Material Safety Data Sheet Before Using
- For Exterior Use Only
- Apply In A Well Ventilated Area
- Close Container When Not In Use
- Environmental Information Is On The Material Safety Data Sheet
- Do Not Reuse Empty Container
- Keep Out Of Reach Of Children
- Avoid Breathing Vapors And Contact With Eyes And Skin. Do Not Take Internally
- Wear Eye Protection And Gloves When Applying

Ingredients:	CAS No.
Petroleum Asphalt	8052-42-4
Fiber	Mixture
Mineral Spirits	64742-88-7
Polymer	9003-55-8

Professional Grade Neoprene Roof Cement

Revised: 01/11